

GLORY

CI-10

Compact cash recycling system



reddot design award
winner 2012

The CI-10 compact cash recycling solution removes the need for staff to handle cash at the point of sale. When integrated into your existing POS system the CI-10 securely automates cash handling at payment positions minimising the risk of errors and shrinkage while enhancing staff productivity and customer service.

UA Hryvnya



As part of our CASHINFINITY™ solution, the CI-10 compact cash recycling system is stylishly designed for easy integration into cash desks and self-checkouts.

	CI-10B (banknote recycler)	CI-10C (coin recycler)
Dimensions (W × D × H)	240 × 483 × 750 – 850mm 9.4" × 19" × 29.5" – 33.5" (height can be adjusted)	240 × 483 × 750 – 850mm 9.4" × 19" × 29.5" – 33.5" (height can be adjusted)
Weight	60 kg / 132lbs.	59 kg / 130lbs.
Function	"Follow me" LED sign Two ways to deposit/dispense, loose notes and interface cassette Exit shutter Error recovery animation Slide extension unit / Low slide extension unit	"Follow me" LED sign Reject foreign object Collection throughoutlet Error recovery animation Slide extension unit / Low slide extension unit
Number of recycle modules	3 recycle modules Free layout recycle module	8 recycle modules Free layout recycle module
Capacity	100 notes / recycle	10 UA Hryvnya 200 coins 5 UA Hryvnya 230 coins 2 UA Hryvnya 260 coins 1** UA Hryvnya 280 coins 0.50 UA Hryvnya 180 coins 0.10 UA Hryvnya 330 coins
Other currencies	100 notes / recycle	Please contact us for further information
Coin overflow tray capacity		<Options> Standard type – 500 coins

	CI-10B (banknote recycler)	CI-10C (coin recycler)
Collection capacity	Selectable collection 450 notes (SCC) 300 notes (IFC)	
Total capacity of banknotes/coins	750 notes (SCC) 600 notes (IFC)	Depends on a recycle module configuration
Deposit Capacity of inlet: Speed of cash in:	30 notes 3 notes / sec	50 coins 5 coins / sec
Dispensing Capacity of outlet: Speed of cash out:	10 notes 3 notes / sec	50 coins 4 coins / sec
Recognition unit	Counterfeit detection <Option> Fit / Unfit detection	Counterfeit detection
Currencies	UA Hryvnya Other currencies on request	UA Hryvnya Other currencies on request
Terminal	FCC included (Controls CI-10B, CI-10C) Slide extension unit: FCC must be located inside of slide extension unit of CI-10B. Low slide extension unit: FCC must be located outside of low slide extension unit of CI-10B.	
Supply voltage range	AC100V – 240V	AC100V – 240V
Nominal frequency	50/60Hz	50/60Hz
Approval	CE, UL	CE, UL

*SCC: Stacking collection cassette, IFC: Interface cassette. The capacity of coins is calculated in 0,10 UA Hryvnya. The capacity of coins is calculated in 1 UA Hryvnya (2018). The CI-10 was awarded with the "red dot award: product design 2012". Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds quoted in this brochure are as tested by GLORY LTD. They may vary depending on usage conditions and are not guaranteed.

Related solutions...

CI-100

Fast secure cash processing and storage in the back office.



CI-SERVER

Centralised management of cash throughout a store in the front and back office.



CI-200

Large capacity, high speed solution for back office cash management.



Innovative Banking Systems LLC

Timiryazevska str., 2, Kiev 01014 Ukraine; phone: 044 495 00 76; e-mail: info@ibs.kiev.ua www.ibs.kiev.ua