

GLORY

RBG-208i

Teller cash recycler

Whether you're looking to transform your branches or simply improve efficiency for increased profitability, the RBG-208 will support your strategy. Enabling open plan layouts, reduced start / end of day processes, faster teller transactions, redeployment of staff and enhanced customer experience – the RBG-208 delivers.



RBG-208i teller cash recyclers deliver an intuitive, secure, flexible and integrated teller automation solution to address the real needs of your customers and staff.

- **8 Roll storage modules** with a capacity of up to 600 banknotes each.
- Increased processing speed for large deposits without interruption thanks to a unique continuous feed hopper.
- Simultaneous processing of different currencies.
- Wide variety of safes, locks and alarm equipment to meet your specific security requirements.
- Regular upgrades and testing to national and international banking requirements and standards.
- Optional collection cassette with a capacity of around 2,000 banknotes.
- Serial number recognition allowing deposited notes to be tracked and the usage of the RBG-200 as a customer operated device.

Features	8 roll storage modules (RSM) Up to 600 notes per RSM 1 intelligent storage module (ISM) Input hopper capacity: Max. 300 notes with continuous feed Output hopper capacity: Max. 150 notes Built-in fitness sorting
Safe	UL 291
Lock	LaGard 39E Standard
Alarm	Prepared for alarm integration
Options	CEN L / III / IV safe 2 additional RSMs or collection cassette Colour touch panel user interface Serial number recognition Alarm

Speed	Deposit: 7 notes per second Dispense: 6 notes per second
Power consumption	Sleep Mode: 72 Watt Standby: 120 Watt Withdrawal: 720 Watt Deposit: 720 Watt
Noise emission	Standby: 50.0 dBA Withdrawal: 67.7 dBA Deposit: 67.7 dBA
Power supply	100 – 240 V, 50/60 Hz
Dimensions (H × W × D)	RBG UL 291: 844 × 420 × 1046mm
Weight	RBG UL 291: 350 kg maximum
Environmental conditions	Operation: +5° to +35° Celsius 20% to 80% relative humidity Transport and storage: -5° to +45° Celsius 10% to 80% relative humidity

*Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds quoted in this brochure are as tested by GLORY LTD. They may vary depending on usage conditions and are not guaranteed.



This mark indicates the product meets Glory's environmental standards.

Related solutions...

CASHINSIGHT™ ASSURE

CashInsight Assure facilitates the operation of cash handling devices, providing immediate teller productivity.



CASHINSIGHT™ BRIDGE

Continuous performance monitoring and remote device management solution.



RCW-100

A compact coin recycling system, enabling automated cash handling at teller positions.



Innovative Banking Systems LLC

Timiryazevska str., 2, Kiev 01014 Ukraine; phone: 044 495 00 76; e-mail: info@ibs.kiev.ua www.ibs.kiev.ua