

GLORY

CI-30B

Banknote deposit solution
for Retailers



reddot award 2018
winner industrial design

A scalable banknote deposit automation device with flexible banknote storage options, advanced authentication and sorting features. CI-30B facilitates large quantities of banknotes to be deposited by Retailers, into a secure device, within their back office environment. Deposits are processed quickly and efficiently, eliminating manual cash handling procedures and reducing cash processing costs.



Available with either 2 banknote stacking safe bags or 3 high capacity cassettes, CI-30B can be deployed to meet varying customer needs, such as mixed note storage or by note classification; fit, unfit, denomination.

CI-30B is an intelligent banknote deposit solution with a large banknote storage capacity (three cassettes/ two stacking safe bags) and secure UL-291 or CENIII safe options. With advanced authentication and sorting features, CI-30B is designed to address high-volume banknote deposit requirements and numerous retail back-office cash handling processes.

Banknote inlet capacity	300 notes	
Banknote outlet capacity	100 notes	
Feed direction	Long-edge first	
Transfer speed	600 notes per minute	
Banknote storage	Collection cassette	Stacking safe bag
	2,500* notes (notes per cassette)	3,500* notes (notes per safe bag)
	3 cassettes per device	2 safe bags per device
	Total 7,500 notes	Total 7,000 notes
	3 cassettes as standard	2 pouches as standard
*Capacity dependent on condition of notes	*2,500 notes applies to 0.11mm per note or under	*3,500 notes applies to 0.11mm per note or under
Safe	Safe: UL-291 24-hour (Safe lock: LAGARD lock)	
	Safe: CEN III (Safe lock: LAGARD lock)	

Access	Front service
Operator display	Colour touch panel
	7 inches
Dimensions (W × D × H)	UL-291 24-hour safe: 550mm × 831mm × 1,225mm 21.7" × 32.7" × 48.2"
	CEN III safe: 550mm × 859mm × 1,300mm 21.7" × 33.8" × 51.2"
Weight	UL-291 24-hour safe – Cassette: 450kg / 992 lbs. – Stacking safe bag: 476kg / 1,050 lbs.
	CEN III safe – Cassette: 645kg / 1,421 lbs. – Stacking safe bag: 682kg / 1,504 lbs.
Supply voltage range	AC 100V – AC 240V
Nominal frequency	50/60 Hz
Approvals and certifications	UL, CE, CB, IEC 60950

*Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds quoted in this brochure are as tested by GLORY LTD. They may vary depending on usage conditions and are not guaranteed.

Related solutions...

CI-10

Compact cash recycling solution, enabling automated cash handling at point of sale positions.



CI-100

Fast secure cash processing and storage in the back office.



CI-SERVER

Centralised management of cash throughout a store in the front and back office.



Innovative Banking Systems LLC

+38 (044) 495 00 76 info@ibs.kiev.ua

www.ibs.kiev.ua

2, Sadovo-Botanicna St., Kiev, Ukraine, 01014.