

# DN Series<sup>®</sup> 300

## Lobby Monofunctional Cash Dispenser



With the highest cash capacity in the smallest footprint, the DN Series<sup>®</sup> 300 minimizes complexity and cost by design. Its compact and reliable architecture supports leaner, more agile self-service networks, unlocking new levels of efficiency, profitability and next-gen security while delivering a highly differentiated consumer experience.

The DM7V cash dispensing module delivers a powerful combination of capacity, precision, and reliability that sets a new benchmark in ATM technology. Its integrated, non-split module architecture ensures compactness without compromising functionality, while enabling faster serviceability and simplified component handling across the entire cash cycle.



**More  
Personalized**

Engaging, consistent, research-based design coupled with powerful Vynamic Marketing<sup>™</sup> enables you to personally connect with consumers at the intersection of physical and digital channels.



**More  
Integrated**

A common platform supported by leading software and services ensures more seamless integration into your organization's channel ecosystem.



**More  
Available**

DN AllConnect<sup>SM</sup> Data Engine, an intelligent data-driven service architecture, maximizes the availability of the globally proven 7<sup>th</sup> generation dispensing module.



**More  
Efficient**

New functionality offers new opportunities to migrate transactions and engage consumers through the self-service channel.



**More  
Future-Ready**

Now you can offer cash dispense today and migrate to cash recycling tomorrow with the industry's most flexible self-service terminal in the smallest footprint.



**More  
Sustainable**

Built for a greener future: DN Series<sup>®</sup> minimizes power use, reduces service and CIT trips, and optimizes resources—supporting your sustainability goals at every step.



**More  
Secure**

Layered security features protect against traditional and emerging physical, data and cyber threats.



**CROSS-PLATFORM MEDIA ENGINES****DM7V Engine (7<sup>th</sup> Generation Dispensing Module)**

- Dispense up to 60-note bundle
- Standard Dispensing Cassette: 420 mm note stacking capacity per cassette
- Dual Dispensing Cassette: 195 mm and 139 mm note stacking capacity for dispensing in one cassette
- Dispense 3 denominations, or up to 6 with dual cassettes in the standard version
- Dispense 4 denominations, or up to 8 with dual cassettes in the high capacity version
- Retract/reject cassette

**ENHANCED SECURITY****Physical**

- Portrait, cash slot and environmental surveillance camera options
- Security Safes: UL 291 Level 1, CEN I, CEN III EX Gas, CEN IV EX Gas
- Variety of alarm options
- Electronic or mechanical safe locks
- Anti-cash-trapping sensor

**Data**

- Consumer awareness mirrors
- Encrypting PIN pad
- PIN pad shield
- Anti-skimming card readers
- Illuminated Privacy Panels

**Cyber**

- Trusted Device Communication
- Basic Endpoint Security
- CryptTA Stick secure service access
- Vynamic® Security
- Trusted Platform Module (TPM)
- AI enabled TILT Dispense Management to deter and minimize jackpotting loss

**Display**

- 15" with function keys and/or touchscreen
- 19" portrait or landscape touchscreen
- Vandal-resistant display
- Supports multi-touch
- Standard or high-bright LCD
- Privacy filter

**Processor**

- Intel® i5
- Intel® Active Management Technology (AMT)
- Solid state drives

**Accessibility**

- Compliant with regional height and reach requirements
- Audio options
- 2-way video camera/microphone
- User guide lights customizable with branding colors

**ID Devices**

- EMV motorized, dip, ActivEdge™ and/or contactless card readers
- Barcode scanner 1D/2D
- Fingerprint reader

**Printers**

- 80 mm thermal receipt printer
- Journal printer

**Serviceability**

- Front or rear load
- 10.1" service display on rear load systems
- Integrated with DN AllConnect Services™ Architecture

**Platform Software & Operating System**

- ProBase/C
- Windows®

**Application Software**

- Vynamic® Software

**Dimensions (HxWxD)**

1319 mm x 450 mm x 711 mm (UL)  
 (51.92 in x 17.71 in x 27.99 in) (UL)

1319mm x 450mm x 780 mm (CEN)  
 (51.92 in x 17.71 in x 30.70 in) (CEN)

See installation manual for other configurations and installation parameters.

\*Components and technologies vary by region and are subject to availability